



MATERIAL SAFETY DATA SHEET

MSDS Number: 00057
Product Name: FM-200

Effective Date: 4/7/98
Page: 1 of 9

SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:	FM-200		
Manufacturer:	Great Lakes Chemical Corporation		
Address:	P.O. Box 2200		
City:	West Lafayette		
State:	Indiana		
Zip:	47996-2200		
Emergency Telephone Number:	1-800-949-5167		
Information Telephone Number:	1-765-497-6100	Fax:	1-765-497-6123
Chemtrec Phone:	1-800-424-9300		
Effective Date:	4/7/98		
Supercede Date:	8/11/97		
MSDS Prepared By:	Regulatory Affairs Department/Great Lakes Chemical Corporation		
Synonyms:	1,1,1,2,3,3,3-Heptafluoropropane, 2H-Heptafluoropropane		
Product Use:	Fire extinguishing, fire suppression, explosion suppression and inerting agent		
Chemical Name:	1,1,1,2,3,3,3-Heptafluoropropane		
Chemical Family:	Halogenated alkane		

Additional Information

No information available

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	%	EXPOSURE LIMITS
1,1,1,2,3,3,3-Heptafluoropropane	431890	>99	Y (Hazardous) Not established (OSHA PEL TWA) Not established (OSHA PEL STEL) Not established (OSHA PEL CEIL) Not established (ACGIH TLV TWA) Not established (ACGIH TLV STEL) Not established (ACGIH TLV CEIL)

*Mixture. Indented chemicals components of mixture.

Additional Information

No information available

MATERIAL SAFETY DATA SHEET

MSDS Number: 00057
Product Name: FM-200

Effective Date: 4/7/98
Page: 2 of 9

SECTION III - HAZARDS IDENTIFICATION

Emergency Overview:	Colorless gas Odorless Direct eye or skin contact with the liquid or cold gas can cause chilling or possibly frostbite of exposed tissues. May cause central nervous system effects. Inhalation of high concentrations can be harmful or fatal due to oxygen deprivation and/or heart irregularities.
Relevant Routes of Exposure:	Inhalation
Signs and Symptoms of Overexposure:	Symptoms similar to oxygen deprivation (headache, nausea, dizziness or loss of consciousness) may result from overexposure by inhalation. Heart irregularities such as irregular pulse or heart palpitations may indicate cardiac sensitivity. Cold, white or discolored skin or in severe cases blistering, can be a sign of frostbite caused by cold liquids or gases.
Medical Conditions Generally Aggravated By Exposure:	Persons with preexisting cardiac, respiratory, or central nervous system disorders may be more susceptible to effects of an overexposure. The use of epinephrine or similar compounds can increase susceptibility to heart irregularities caused by excessive exposure to these types of compounds.
Potential Health Effects:	See Section XI for additional information.
Eyes:	Direct eye contact with the liquid or cold gas can cause chilling or possibly frostbite of exposed tissues.
Skin:	Direct skin contact with the liquid or cold gas can cause chilling or possibly frostbite of exposed tissues.
Ingestion:	Not expected to be a hazard in normal industrial use.
Inhalation:	Inhalation of high concentrations can be harmful or fatal due to oxygen deprivation and/or heart irregularities (arrhythmias). Misuse of the product by deliberately inhaling high concentrations of this gas could cause death without warning.
Carcinogenicity:	
NTP:	No
IARC:	No
OSHA:	No
ACGIH:	No
OTHER:	No

Additional Information

No information available

SECTION IV - FIRST AID MEASURES

Eyes:	Flush with water. Get medical attention.
Skin:	Flush with water; if frostbite occurs get medical attention.
Ingestion:	No information available
Inhalation:	Remove person to fresh air; if not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical

MATERIAL SAFETY DATA SHEET

MSDS Number: 00057
Product Name: FM-200

Effective Date: 4/7/98
Page: 3 of 9

SECTION IV - FIRST AID MEASURES

Antidotes: attention.
No information available

**Notes to Physicians and/or
Protection for First-Aiders:** The use of epinephrine or similar compounds can increase susceptibility to heart irregularities caused by excessive exposure to these types of compounds.

Additional Information

No information available

SECTION V - FIRE FIGHTING MEASURES

**Flammable Limits in Air (%
by Volume):** Not applicable

Flash Point: Nonflammable gas

Autoignition Temperature: Not available

Extinguishing Media: All conventional media are suitable.

Fire Fighting Instructions: Keep cylinders cool with a water spray applied from a safe distance. Use a self-contained breathing apparatus if containers rupture or release under fire conditions. Do not allow reentry into areas where this material has been released without first ventilating to remove products of combustion/decomposition.

**Unusual Fire and Explosion
Hazards:** Although containers of our product are provided with pressure and temperature relief devices, containers can rupture if exposed to localized heat. Thermal decomposition will generate toxic and corrosive gases.

**Flammability Classification:
Known or Anticipated
Hazardous Products of
Combustion:** Nonflammable gas

Decomposition by elevated temperatures (fire conditions, glowing metal surfaces) may generate hazardous decomposition products common to other CFCs, HCFCs or HBFCs. These can include hydrogen fluoride, carbon monoxide, carbon dioxide and others.

Additional Information

No information available

SECTION VI - ACCIDENTAL RELEASE MEASURES

**Accidental Release
Measures:** Evacuate the area and ventilate. Do not enter areas where high concentrations may exist (especially confined or poorly ventilated areas) without appropriate protective equipment including a self-contained breathing apparatus.

Personal Precautions: See Section VIII.

Environmental Precautions: No information available

Additional Information

No information available

MATERIAL SAFETY DATA SHEET

MSDS Number: 00057
Product Name: FM-200

Effective Date: 4/7/98
Page: 4 of 9

SECTION VII - HANDLING AND STORAGE

Handling: Use the same type of precautions as would be used in handling any cryogenic gas. Protect container from damage. Handle in well-ventilated areas. When this material is used as a firefighting agent in fixed or portable extinguishing systems, follow manufacturer's instructions for operation, inspection, maintenance and repair of the system.

Storage: Store in a cool, dry, well-ventilated area away from incompatible materials.
Keep container tightly closed.

Other Precautions: No information available

Additional Information

No information available

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: No information available

Ventilation Requirements: Use local ventilation to minimize exposure to gas.
Use mechanical ventilation for general area control.

Personal Protective Equipment:

Eye/Face Protection: Chemical splash goggles when handling liquid

Skin Protection: Use lined neoprene gloves if handling liquid.
Clothing designed to minimize skin contact

Respiratory Protection: Wear a NIOSH/MSHA approved self-contained breathing apparatus in emergency situations.
Consult the OSHA respiratory protection information located at 29CFR 1910.134 and the American National Standard Institute's Practices of Respiratory Protection Z88.2.

Other Protective Clothing or Equipment: No information available

Exposure Guidelines: See Section II.

Work Hygienic Practices: Wash thoroughly after handling.
Wash contaminated clothing before reuse.
Make sure piping is empty before doing maintenance work.

Additional Information

No information available

SECTION IX - PHYSICAL & CHEMICAL PROPERTIES

Appearance: Colorless gas

Boiling Point: -16.4 degrees C (3 degrees F)

Bulk Density: Not available

Color: Colorless

Decomposition

MATERIAL SAFETY DATA SHEET

MSDS Number: 00057

Effective Date: 4/7/98

Product Name: FM-200

Page: 5 of 9

SECTION IX - PHYSICAL & CHEMICAL PROPERTIES

Temperature:	Not available
Evaporation Rate:	Not available
Freezing Point:	Not available
Heat Value:	Not available
Melting Point:	-131 degrees C (-204 degrees F)
Molecular/Chemical Formula:	C3HF7
Molecular Weight:	170
Octanol/Water Partition Coefficient:	Not available
Odor:	Odorless
Odor Threshold:	Not available
Particle Size:	Not available
Percent Volatile:	Not available
pH Value:	Not available
pH Concentration:	Not available
Physical State:	Gas
Reactivity in Water:	Not water reactive
Saturated Vapor Concentration:	Not available
Softening Point:	Not available
Solubility in Water:	260 mg/L
Specific Gravity or Density (Water=1):	1.46
Vapor Density:	6.04
Vapor Pressure:	58.8 psia at 70 degrees F (21 degrees C)
Viscosity:	Not available
Volatile Organic Compounds:	Not available
Water/Oil Distribution Coefficient:	Not available
Weight Per Gallon:	Not available

Additional Information

No information available

SECTION X - STABILITY AND REACTIVITY

Stability: Stable under normal conditions of handling and use.
Conditions to Avoid: None

Incompatibility With Other Materials:

Powdered metals (ex. Al, Mg, or Zn) and strong alkalis, oxidizers or reducing agents are not compatible with this and most other halogenated organic compounds.

Hazardous Decomposition Products:

Thermal decomposition may produce the following:

MATERIAL SAFETY DATA SHEET

MSDS Number: 00057

Effective Date: 4/7/98

Product Name: FM-200

Page: 6 of 9

SECTION X - STABILITY AND REACTIVITY

Hazardous Polymerization: Hydrogen fluoride
Carbon monoxide and carbon dioxide
Will not occur

Conditions to Avoid: None

Additional Information

No information available

SECTION XI - TOXICOLOGICAL INFORMATION

VALUE (LD50 OR LC50)	ANIMAL	ROUTES	COMPONENTS
>788,696 ppm/4H	Rat		

MATERIAL SAFETY DATA SHEET

MSDS Number: 00057
Product Name: FM-200

Effective Date: 4/7/98
Page: 7 of 9

No information available

SECTION XII - ECOLOGICAL INFORMATION

Ecological Information: No information available

Additional Information

No information available

SECTION XIII - DISPOSAL CONSIDERATIONS

Disposal Considerations: Non-contaminated product is reclaimable. Contact Great Lakes Chemical Corporation for information. Otherwise, dispose of waste in an approved chemical incinerator equipped with a scrubber as allowed by current Local, State/Province, Federal/Canadian laws and regulations.

Additional Information

No information available

SECTION XIV - TRANSPORT INFORMATION

U.S. DOT

Proper Shipping Name: Heptafluoropropane
Hazard Class: 2.2
ID Number: UN3296
Packing Group: N/A
Labels: Nonflammable gas
Special Provisions: N/A
Packaging Exceptions: 306
Non-Bulk Packaging: 304
Bulk Packaging: 314, 315
Air/Rail Limit: 75 kg
Air Cargo Limit: 150 kg
Vessel Stowage: A
Other Stowage: N/A
Reportable Quantity: N/A

AIR - ICAO OR IATA

Proper Shipping Name: Heptafluoropropane
Hazard Class: 2.2
ID Number: UN3296
Subsidiary Risk: N/A
Packing Group: N/A
Hazard Labels: Nonflammable gas
Packing Instructions: 200
Air Passenger Limit Per Package: 75 kg
Packing Instruction - Cargo: 200
Air Cargo Limit Per Package: 150 kg
Special Provisions Code: N/A

WATER - IMDG

MATERIAL SAFETY DATA SHEET

MSDS Number: 00057
Product Name: FM-200

Effective Date: 4/7/98
Page: 8 of 9

SECTION XIV - TRANSPORT INFORMATION

Proper Shipping Name: Heptafluoropropane
Hazard Class: 2.2
ID Number: UN3296
Packing Group: N/A
Subsidiary Risk: N/A
Medical First Aid Guide Code: 350

Additional Information

EmS No. 2-09

SECTION XV - REGULATORY INFORMATION

U.S. Federal Regulations: The components of this product are either on the TSCA Inventory or exempt (i.e. impurities, a polymer complying with the exemption rule at 40 CFR 723.250) from the Inventory.
State Regulations: None known
International Regulations: This material (or each component) is listed on the following inventories:
EU - EINECS

Canadian WHMIS Hazard Class and Division = A.

SARA Hazards:

Acute: Yes
Chronic: No
Reactive: No
Fire: No
Pressure: No

Additional Information

The above regulatory information represents only selected regulations and is not meant to be a complete list.

SECTION XVI - OTHER INFORMATION

NFPA Codes:

Health: 1
Flammability: 0
Reactivity: 0
Other: 0

HMIS Codes:

Health: 1
Flammability: 0
Reactivity: 0
Protection: X

Label Statements: Not available

Other Information:

Abbreviations:
(L) = Loose bulk density in g/ml
LOEC = Lowest observed effect concentration

MATERIAL SAFETY DATA SHEET

MSDS Number: 00057

Effective Date: 4/7/98

Product Name: FM-200

Page: 9 of 9

SECTION XVI - OTHER INFORMATION

MATC = Maximum acceptable toxicant concentration

NA = Not available

N/A = Not applicable

NL = Not limited

NOEC = No observed effect concentration

NOEL = No observable effect level

NR = Not rated

(P) = Packed bulk density in g/ml

PNOC = Particulates Not Otherwise Classified

PNOR = Particulates Not Otherwise Regulated

REL = Recommended exposure limit

TS = Trade secret

Additional Information

Information on this form is furnished solely for the purpose of compliance with OSHA's Hazard Communication Standard, 29CFR 1910.1200 and The Canadian Environmental Protection Act, Canada Gazette Part II, Vol. 122, No. 2 and shall not be used for any other purpose.

Revision Information:

Section XIV - IMDG Code Information

Section XV - Regulatory Information